











- [15] Z. Hao, J. Zhang, and K. Li, "Study on the angle of stationary crescent of radial compensation for inner mesh gear pump," *Mechanical Transmission*, vol. 36, no. 6, pp. 8-14, 2012. (in Chinese with English abstract)
- [16] S. Wen, and P. Huang, *The principle of Tribology*, Tsinghua University Press: Beijing, 2008.
- [17] W. Xu, Y. Yin, and Q. Tian, "Tribological properties of the Fe based gear pump side plate prepared by power metallurgy method," *Power Metallurgy Industry*, vol. 21, no. 3, pp. 20-23, 2011. (in Chinese with English abstract)
- [18] W. Shen, "The use of gear pump for continuous casting of copper alloy plate," China, 201110360789, pp. 2-22, 2012.
- [19] X. Xu, "A gear pump gear side end face wear resistance," China, 200810224087, 2009-02-18.
- [20] C. He, *Hydraulic Components*, Beijing: China Machine Press, 1985, (in Chinese)
- [21] G. Yao, "Analysis of oil film force of meshing tooth gear involute few teeth difference internal," *Journal of East China University of Science and Technology*, vol. 11, no. 1, pp. 121-127, 1985.
- [22] L. Wang, "Analysis of static and dynamic characteristics on spiral oil wedge hydrodynamic bearing considering input pressure," *Lubrication Engineering*, vol. 33, no. 11, pp. 77-80, 2008. (in Chinese with English abstract)
- [23] Y. Li, and K. Liu, "Study of lubricating state on meshing surface in external gear lubrication pump without regard to trapped volume," *Lubrication Engineering*, vol. 33, no. 5, pp. 42-45, 2008. (in Chinese with English abstract)
- [24] S. Chen, and C. Lu, "The analysis of structure on a novel spiral oil wedge hybrid Journal Bearing," *Lubrication Engineering*, vol. 182, no. 10, pp. 15-21, 2006. (in Chinese with English abstract)
- [25] Q. Bi, J. Ling, and C. Zhang, "Analysis on structure feature of IGP high pressure low noise internal gear pumps," *Machine Tool & Hydraulics*, vol. 38, no.2, pp. 50-52, 2010. (in Chinese with English abstract)
- [26] B. Paffoni, R. Proghi, and R. Gras, "Teeth clearance effects upon pressure and film thickness in a trochoidal hydrostatic gear pump," In: *Proceedings of the Institution of Mechanical Engineers, Part G: Journal of Aerospace Engineering*, vol. 218, no. 4, pp. 247-256, 2004.
- [27] Z. Xu, D. Gong, and J. Zhao, "Optimal processing method of hybrid bearing oil wedge," *Manufacturing Technology & Machine Tool*, no. 5, pp. 115-116, 2012. (in Chinese with English abstract).

---

Received: October 3, 2014

Revised: January 5, 2015

Accepted: January 17, 2015

© Zhenxing et al.; Licensee Bentham Open.

This is an open access article licensed under the terms of the Creative Commons Attribution Non-Commercial License (<http://creativecommons.org/licenses/by-nc/3.0/>) which permits unrestricted, non-commercial use, distribution and reproduction in any medium, provided the work is properly cited.

RETRACTED ARTICLE